


REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	CJJ 11/18/2014	~	ZQJ 11/18/2014
B	整理图面	CJJ 11/18/2014	~	ZQJ 11/18/2014
C	整理图面	CJJ 11/18/2014	~	ZQJ 11/18/2014
D	ADD P/N CODE	CJJ 11/18/2014	~	

- Notes:
- Insulation material: PVC  
Color: Gray
  - Specifications:
    - Rating: 300V
    - Conductor Size: 28AWG or 30AWG.
    - Insulation resistance: 100MΩ/km min.
  - Applications:
    - Internal wiring of computers, electronic exchanges, measurement control devices, business machines, communication devices, and other electronic equipment.
  - Product Number Code  
LL1049-1- X X X X X - X

- Packing Type ®
  - 30.5: 30.5m/reel
  - 61.0: 60.1m/reel
  - 76.5: 76.5m/reel
  - 150: 150m/reel
- Edge mark
  - R: Red mark
  - F: Flower mark
- Wire diameter
  - 1:  $\phi 0.100$  (30AWG)
  - 2:  $\phi 0.127$  (28AWG)
- Wire AWG
  - 28: 28AWG
  - 30: 30AWG
- Cable color
  - A: Gray
- No. Of positions
  - 06: 6pin
  - 64: 64pin

Number	Dimensions			Max. conductor resistance DC 20°C Ω/m
	TP(mm)	W(mm)	Tolerance	
10	11.43	12.70	±0.30	φ0.100 < 0.397
14	16.51	17.78	±0.30	
16	19.05	20.32	±0.30	
20	24.13	25.40	±0.30	
24	29.21	30.48	±0.30	
26	31.75	33.02	±0.30	
30	36.83	38.10	±0.30	φ0.127 < 0.237
34	41.91	43.18	±0.40	
40	49.53	50.80	±0.40	
50	62.23	63.50	±0.40	
60	74.93	76.20	±0.40	
64	80.01	81.28	±0.40	

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION	TITLE		
X.	±0.60	X.	±5°	UNITS	UL2651 FLAT CABLE 1.27MM		
.X	±0.38	.X	±3°	SHEET SIZE	mm		
.XX	±0.25	.XX	±2°	A4	SERIES	LL1049-1	
DRAWING TYPE		CUSTOMER		 <b>慈溪蓝翎电子有限公司</b> CITX LANLING ELECTRONICS CO., LTD.			
SCALE	1:1	SHEET	1 OF 1				
DRAWING NO.							